

### §1910.133

### 29 CFR Ch. XVII (7-1-03 Edition)

(ii) Changes in the types of PPE to be used render previous training obsolete; or

(iii) Inadequacies in an affected employee's knowledge or use of assigned PPE indicate that the employee has not retained the requisite understanding or skill.

(4) The employer shall verify that each affected employee has received and understood the required training through a written certification that contains the name of each employee trained, the date(s) of training, and that identifies the subject of the certification.

(g) Paragraphs (d) and (f) of this section apply only to §§1910.133, 1910.135, 1910.136, and 1910.138. Paragraphs (d) and (f) of this section do not apply to §§1910.134 and 1910.137.

[39 FR 23502, June 27, 1974, as amended at 59 FR 16334, Apr. 6, 1994; 59 FR 33910, July 1, 1994]

#### **§1910.133 Eye and face protection.**

(a) *General requirements.* (1) The employer shall ensure that each affected employee uses appropriate eye or face protection when exposed to eye or face hazards from flying particles, molten metal, liquid chemicals, acids or caus-

tic liquids, chemical gases or vapors, or potentially injurious light radiation.

(2) The employer shall ensure that each affected employee uses eye protection that provides side protection when there is a hazard from flying objects. Detachable side protectors (e.g. clip-on or slide-on side shields) meeting the pertinent requirements of this section are acceptable.

(3) The employer shall ensure that each affected employee who wears prescription lenses while engaged in operations that involve eye hazards wears eye protection that incorporates the prescription in its design, or wears eye protection that can be worn over the prescription lenses without disturbing the proper position of the prescription lenses or the protective lenses.

(4) Eye and face PPE shall be distinctly marked to facilitate identification of the manufacturer.

(5) The employer shall ensure that each affected employee uses equipment with filter lenses that have a shade number appropriate for the work being performed for protection from injurious light radiation. The following is a listing of appropriate shade numbers for various operations.

## Filter Lenses for Protection Against Radiant Energy

| Operations                                       | Electrode Size 1/32 in. | Arc Current         | Minimum* Protective Shade |
|--|-------------------------|---------------------|---------------------------|
| Shielded metal arc welding                       | Less than 3 .....       | Less than 60 .....  | 7                         |
|  | 3-5 .....               | 60-160 .....        | 8                         |
|  | 5-8 .....               | 160-250 .....       | 10                        |
|  | More than 8 .....       | 250-550 .....       | 11                        |
| Gas metal arc welding and flux cored arc welding |                         | less than 60 .....  | 7                         |
|  |                         | 60-160 .....        | 10                        |
|  |                         | 160-250 .....       | 10                        |
|  |                         | 250-500 .....       | 10                        |
| Gas Tungsten arc welding                         |                         | less than 50 .....  | 8                         |
|  |                         | 50-150 .....        | 8                         |
|  |                         | 150-500 .....       | 10                        |
| Air carbon Arc cutting                           | (Light) .....           | less than 500 ..... | 10                        |
|  | (Heavy) .....           | 500-1000 .....      | 11                        |
| Plasma arc welding                               |                         | less than 20 .....  | 6                         |
|  |                         | 20-100 .....        | 8                         |
|  |                         | 100-400 .....       | 10                        |
|  |                         | 400-800 .....       | 11                        |
| Plasma arc cutting                               | (light)** .....         | less than 300 ..... | 8                         |
|  | (medium)** .....        | 300-400 .....       | 9                         |
|  | (heavy)** .....         | 400-800 .....       | 10                        |
| Torch brazing                                    |                         | .....               | 3                         |
| Torch soldering                                  |                         | .....               | 2                         |
| Carbon arc welding                               |                         | .....               | 14                        |

## Filter Lenses for Protection Against Radiant Energy

| Operations      | Plate thickness— inches | Plate thickness—mm | Minimum* Protective Shade |
|-----------------|-------------------------|--------------------|---------------------------|
| Gas Welding:    |                         |                    |                           |
| Light           | Under 1/8 .....         | Under 3.2 .....    | 4                         |
| Medium          | 1/8 to 1/2 .....        | 3.2 to 12.7 .....  | 5                         |
| Heavy           | Over 1/2 .....          | Over 12.7 .....    | 6                         |
| Oxygen cutting: |                         |                    |                           |
| Light           | Under 1 .....           | Under 25 .....     | 3                         |
| Medium          | 1 to 6 .....            | 25 to 150 .....    | 4                         |
| Heavy           | Over 6 .....            | Over 150 .....     | 5                         |

\* As a rule of thumb, start with a shade that is too dark to see the weld zone. Then go to a lighter shade which gives sufficient view of the weld zone without going below the minimum. In oxyfuel gas welding or cutting where the torch produces a high yellow light, it is desirable to use a filter lens that absorbs the yellow or sodium line in the visible light of the (spectrum) operation.

\*\* These values apply where the actual arc is clearly seen. Experience has shown that lighter filters may be used when the arc is hidden by the workpiece.

## § 1910.134

## 29 CFR Ch. XVII (7–1–03 Edition)

(b) *Criteria for protective eye and face devices.* (1) Protective eye and face devices purchased after July 5, 1994 shall comply with ANSI Z87.1–1989, “American National Standard Practice for Occupational and Educational Eye and Face Protection,” which is incorporated by reference as specified in § 1910.6, or shall be demonstrated by the employer to be equally effective.

(2) Eye and face protective devices purchased before July 5, 1994 shall comply with the ANSI “USA standard for Occupational and Educational Eye and Face Protection,” Z87.1–1968, which is incorporated by reference as specified in § 1910.6, or shall be demonstrated by the employer to be equally effective.

[59 FR 16360, Apr. 6, 1994; 59 FR 33911, July 1, 1994, as amended at 61 FR 9238, Mar. 7, 1996; 61 FR 19548, May 2, 1996]

### § 1910.134 Respiratory protection.

This section applies to General Industry (part 1910), Shipyards (part 1915), Marine Terminals (part 1917), Longshoring (part 1918), and Construction (part 1926).

(a) *Permissible practice.* (1) In the control of those occupational diseases caused by breathing air contaminated with harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors, the primary objective shall be to prevent atmospheric contamination. This shall be accomplished as far as feasible by accepted engineering control measures (for example, enclosure or confinement of the operation, general and local ventilation, and substitution of less toxic materials). When effective engineering controls are not feasible, or while they are being instituted, appropriate respirators shall be used pursuant to this section.

(2) Respirators shall be provided by the employer when such equipment is necessary to protect the health of the employee. The employer shall provide the respirators which are applicable and suitable for the purpose intended. The employer shall be responsible for the establishment and maintenance of a respiratory protection program which shall include the requirements outlined in paragraph (c) of this section.

(b) *Definitions.* The following definitions are important terms used in the

respiratory protection standard in this section.

*Air-purifying respirator* means a respirator with an air-purifying filter, cartridge, or canister that removes specific air contaminants by passing ambient air through the air-purifying element.

*Assigned protection factor (APF)* [Reserved]

*Atmosphere-supplying respirator* means a respirator that supplies the respirator user with breathing air from a source independent of the ambient atmosphere, and includes supplied-air respirators (SARs) and self-contained breathing apparatus (SCBA) units.

*Canister or cartridge* means a container with a filter, sorbent, or catalyst, or combination of these items, which removes specific contaminants from the air passed through the container.

*Demand respirator* means an atmosphere-supplying respirator that admits breathing air to the facepiece only when a negative pressure is created inside the facepiece by inhalation.

*Emergency situation* means any occurrence such as, but not limited to, equipment failure, rupture of containers, or failure of control equipment that may or does result in an uncontrolled significant release of an airborne contaminant.

*Employee exposure* means exposure to a concentration of an airborne contaminant that would occur if the employee were not using respiratory protection.

*End-of-service-life indicator (ESLI)* means a system that warns the respirator user of the approach of the end of adequate respiratory protection, for example, that the sorbent is approaching saturation or is no longer effective.

*Escape-only respirator* means a respirator intended to be used only for emergency exit.

*Filter or air purifying element* means a component used in respirators to remove solid or liquid aerosols from the inspired air.

*Filtering facepiece (dust mask)* means a negative pressure particulate respirator with a filter as an integral part of the facepiece or with the entire facepiece composed of the filtering medium.